



16645 Heimbach Road
Three Rivers, MI 49093
Phone 269-279-5123
Fax 269-279-6337
www.wfwells.com

2013

W.F. WELLS MODEL F-16-3

Specifications

Capacity.....	Rectangular at 90° 17" High x 20" Wide, Round at 90° 17" Diameter	
Weight Capacity.....	5,000 lbs	
Blade Speed	60-500 SFPM	
Blade Size	1½" X .050" X 16' 8"	
Blade Guide	Carbide with Roller Backup	
Blade Tension.....	Hydraulic	
Bandwheel Size	22"	
Vise	Full Stroke Hydraulic	<u>Voltage</u>
Blade Drive	10 HP, AC Vector Drive	208-60-3
Sawing Force.....	0-750 lbs	230-60-3
Coolant Capacity	15 Gallons	460-60-3
Hydraulic Capacity	20 Gallons	575-60-3
Hydraulic Drive	2 HP Motor	
Work Height.....	35"	
Shipping Weight.....	3,200 lbs	
Electrics	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions.....	101" Length x 50" Width x 88" Height	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Discharge Worktable, 22" W x 48" L with Stock Stop
- Work Light, Wired In
- Blade Break/Stall Switch
- Hydraulic Chip Conveyor, Auger Style
- Hydraulic Holddown, Saw Vise
- Hydraulic Powered Conveyor 21" X 10'
- High Speed Drive & Guides (1¼" Blade) 400-3000 SFPM
- Free Standing Non-Powered Conveyors, 6" Centers

- 21" X 5' X 5,000 lbs Cap. Distributed Weight
- 21" X 10' X 10,000 lbs Cap. Distributed Weight

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

