



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone: (269) 279-5123
 Fax: (269) 279-6337
www.wfwells.com

W.F. WELLS MODEL H-1051-2GRS Grating/Panel

Specifications

Capacity.....	Rectangular, 10" High x 51" Wide, 3° Canted Frame	
Weight Capacity.....	5,000 lbs - with Bed in Full Upper Position	
Blade Speed	60-500 SFPM	
Blade Size	1¼" X .042" X 22' -3" - with Easy Change Tilt Feature	
Blade Guide	Rollers and Carbide Side Blocks	
Blade Tension.....	Full Time Hydraulic	
Bandwheel Size	20"	
Vises.....	Vertical (4), Both Sides of Blade	
	Front and Back Independent	
	with Arma Plate Surface	<u>Voltage</u>
	and Vertical Stationary	
	Datum Rollers	208-60-3
Blade Drive	7½ HP, AC Vector Drive	230-60-3
Sawing Force.....	0-500 lbs	460-60-3
Coolant	Mist System, 32 oz Capacity	
Hydraulic Capacity	20 Gallons	
Hydraulic Drive	2 HP Motor – Full Time	
Saw Bed	35" Work Height	
	Hydraulic Saw Bed Raise/Lower Feature	
	with Replaceable UHMW Wear Surface(s)	
	and Horizontal Infeed and Outfeed Rollers	
Cutting Head Travers	Linear Motion Ball Rail	
Laser Cut Line	Wired In	
Electrics	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions.....	140" Wide x 48" Deep x 86" High	
Shipping Weight.....	4,500 lbs	
Fork Lift Pockets in Base	Side Loaded	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Work Light, Wired In	
Blade Break/Stall Switch	
Conveyors	Consult Factory

Consult Factory for Additional Accessories

*Prices and specifications subject to change without notice

